

2-46 Dual 23-Spindle Line Boring Machine



Optional Individually Controlled Pneumatic Flip Stops



- Telemechanique Control System.
- 132" Fence Length with 4 Flip Stops.
- Dual 23-Spindle Heads for Rapid Production.
- Individual Head Movement with Precision Digital Positioning.
- Powered by Two BALDOR Totally Enclosed Fan Cooled Motors.
- *Optional* "Through Brake" to eliminate breakout when through boring.
- *Optional* Quick Release Chucks
- *Optional* Pneumatic Flip Stops.
- *Optional* 3rd Hold Down For Hard Surface Materials (HPL etc.)
- *Optional* Dust Collection Shrouds.

Individual Precision Head Movement



Optional Dust Collection Shrouds



STANDARD FEATURES & SPECIFICATIONS

- 2 pneumatic index pins.
- 2 pneumatic hold downs.
- Working table height of 37.5"
- Pneumatic foot pedal operation.
- Operating pressure of 80–100 psi.
- Motor turns off when pedal released.
- 32 millimeter centers, distance between first and last drill = 27.7".
- 30" maximum throat adjustment (from fence to point of drill bits on #2 head.)
- 2 independently operated 23-spindle boring heads with heat treated steel helical gears.
- 2 Baldor motors, 3,450 rpm, 2hp – 220 volt (5.8 amps) 60 Hz Three Phase. (440 volt 2.9 amps optional)
- Accepts 10 millimeter flat shank bits, 24 Lefts & 22 Rights with maximum drilling depth of 60mm (30mm with quick release option).
- *Machine weight (approx.) 1110 lbs, crated 1175 lbs. Frame Size: approx. 44" Wide by 48" Deep*

One Year Warranty On Workmanship & Manufacturing



12740 Lakeland Rd
Santa Fe Springs, CA. 90670
(800) 368-2278 (562) 906-1111 Phone • (562) 906-1112 Fax
www.conquestind.com Email: sales@conquestind.com